


Reducing Socket





SIZE	DIMENSIONS		
	Α	В	KG EACH
1/4 x 1/8	18.5	24.9	0.03
3/8 x 1/8	22	24.9	0.04
3/8 x 1/4	22	29	0.04
1/2 x 1/8	26.5	27.5	0.05
1/2 x 1/4	26.5	29.4	0.05
1/2 x 3/8	26.5	31.6	0.06
3/4 x 1/4	32.5	30.4	0.07
3/4 x 3/8	32.5	32.6	0.08
3/4 x 1/2	32.5	32.5	0.09
1 x 1/4	40	34.4	0.16
1 x 3/8	40	40	0.12
1 x 1/2	40	40	0.13
1 x 3/4	40	38	0.15
1-1/4 x 1/2	49	40	0.18
1-1/4 x 3/4	49	41	0.19
1-1/4 x 1	49	45	0.21
1-1/2 x 1/2	55	41	0.22
1-1/2 x 3/4	55	42	0.22
1-1/2 x 1	55	46	0.24
1-1/2 x 1-1/4	55	49	0.24
2 x 1/2	68	45	0.33
2 x 3/4	68	46	0.34
2 x 1	68	50	0.37
2 x 1-1/4	68	53	0.40
2 x 1-1/2	68	54	0.41
2-1/2 x 1-1/2	84	57	0.58
2-1/2 x 2	84	61	0.60
3 x 1-1/2	97.5	60	0.79
3 x 2	97.5	64	0.82
3 x 2-1/2	97.5	67	0.92
4 x 2	124	70	1.32
4 x 2-1/2	124	73	1.84
4 x 3	124	76	1.46

Our Threaded Fittings are produced through the castings process and can be supplied in material 316 with threads according to NPT and BSP.







EXPERT KNOWLEDGE OF THE INDUSTRY

