



SIZE	SCHEDULE 10						SCHEDULE 40					
	A OD	B OD	C	D	E	KG	A OD	B OD	C	D	E	KG
3/4 X 3/8	26.6	17.15	35.2	2.11	2.11	0.08	26.6	17.15	35.2	2.31	2.87	0.09
3/4 X 1/2	26.6	21.3	38.1	2.11	2.11	0.09	26.6	21.3	38.1	2.77	2.87	0.10
1 X 1/2	33.4	21.3	50.8	2.11	2.77	0.09	33.4	21.3	50.8	2.77	3.38	0.13
1 X 3/4	33.4	26.6	50.8	2.11	2.77	0.10	33.4	26.6	50.8	2.87	3.38	0.13
1-1/4 X 1/2	42.1	21.3	50.8	2.11	2.77	0.12	-	-	-	-	-	-
1-1/4 X 3/4	42.1	26.6	50.8	2.11	2.77	0.12	42.1	26.6	50.8	2.87	3.56	0.16
1-1/4 X 1	42.1	33.4	50.8	2.77	2.77	0.13	42.1	33.4	50.8	3.38	3.56	0.18
1-1/2 X 1/2	48.3	21.3	63.5	2.11	2.77	0.15	48.3	21.3	63.5	2.77	3.68	0.26
1-1/2 X 3/4	48.3	26.6	63.5	2.11	2.77	0.16	48.3	26.6	63.5	2.87	3.68	0.26
1-1/2 X 1	48.3	33.4	63.5	2.77	2.77	0.17	48.3	33.4	63.5	3.38	3.68	0.26
1-1/2 X 1-1/4	48.3	42.1	63.5	2.77	2.77	0.20	48.3	42.1	63.5	3.56	3.68	0.26
2 X 1/2	60.3	21.3	76.2	2.11	2.77	0.20	-	-	-	-	-	-
2 X 3/4	60.3	26.6	76.2	2.11	2.77	0.21	60.3	26.6	76.2	2.87	3.91	0.30
2 X 1	60.3	33.4	76.2	2.77	2.77	0.24	60.3	33.4	76.2	3.38	3.91	0.41
2 X 1-1/4	60.3	42.1	76.2	2.77	2.77	0.26	60.3	42.1	76.2	3.56	3.91	0.41
2 X 1-1/2	60.3	48.3	76.2	2.77	2.77	0.27	60.3	48.3	76.2	3.68	3.91	0.41
2-1/2 X 1	73	33.4	76.2	2.77	3.05	0.31	73	33.4	76.2	3.38	5.16	0.77
2-1/2 X 1-1/4	73	42.1	76.2	2.77	3.05	0.34	73	42.1	76.2	3.56	5.16	0.77
2-1/2 X 1-1/2	73	48.3	88.9	2.77	3.05	0.40	73	48.3	88.9	3.68	5.16	0.77
2-1/2 X 2	73	60.3	88.9	2.77	3.05	0.43	73	60.3	88.9	3.91	5.16	0.77
3 X 1	88.9	33.4	88.9	2.77	3.05	0.44	88.9	33.4	88.9	3.38	5.49	1.00
3 X 1-1/4	88.9	42.1	88.9	2.77	3.05	0.44	88.9	42.16	88.9	3.56	5.49	1.00
3 X 1-1/2	88.9	48.3	88.9	2.77	3.05	0.44	88.9	48.3	88.9	3.68	5.49	1.00
3 X 2	88.9	60.3	88.9	2.77	3.05	0.48	88.9	60.3	88.9	3.91	5.49	1.00
3 X 2-1/2	88.9	73	88.9	3.05	3.05	0.55	88.9	73	88.9	5.16	5.49	1.00
4 X 1-1/2	114.3	48.3	101.6	2.77	3.05	0.60	-	-	-	-	-	-
4 X 2	114.3	60.3	101.6	2.77	3.05	0.66	114.3	60.3	101.6	3.91	6.02	1.60
4 X 2-1/2	114.3	73	101.6	3.05	3.05	0.71	114.3	73	101.6	5.16	6.02	1.60
4 X 3	114.3	88.9	101.6	3.05	3.05	0.75	114.3	88.9	101.6	5.49	6.02	1.60
5 X 3	141.3	88.9	127	3.05	3.4	1.20	141.3	88.9	127	5.49	6.55	2.27
5 X 4	141.3	114.3	127	3.05	3.4	1.32	141.3	114.3	127	6.02	6.55	2.50
6 X 3	168.3	88.9	139.7	3.05	3.4	1.50	168.3	88.9	139.7	5.49	7.11	3.95
6 X 4	168.3	114.3	139.7	3.05	3.4	1.62	168.3	114.3	139.7	6.02	7.11	3.95
6 X 5	168.3	141.3	139.7	3.4	3.4	1.75	168.3	141.3	139.7	6.55	7.11	3.57
8 X 4	219.1	114.3	152	3.05	3.76	1.92	219.1	114.3	152	6.02	8.18	6.50
8 X 5	219.1	141.3	152	3.4	3.76	2.01	219.1	141.3	152	6.55	8.18	6.50
8 X 6	219.1	168.3	152	3.4	3.76	2.12	219.1	168.3	152	7.11	8.18	6.50
10 X 6	273	168.3	178	3.4	4.19	5.45	-	-	-	-	-	-
10 X 8	273	219.1	178	3.4	4.19	5.45	-	-	-	-	-	-
12 X 6	323.9	168.3	203.2	3.4	4.57	7.30	-	-	-	-	-	-
12 X 8	323.9	219.1	203.2	3.76	4.57	7.10	-	-	-	-	-	-
12 X 10	323.9	273.1	203.2	4.19	4.57	7.10	-	-	-	-	-	-

Our range of BUTT WELD Concentric Reducers are made to ANSI B16.9 and MSS SP43. They are available in schedule 10-40 thickness and 316/L or 304/L material grades.

Certificates are available upon request.



DELIVERY AS SOON
AS NEXT DAY



EXPERT KNOWLEDGE
OF THE INDUSTRY



WORLD CLASS
CUSTOMER SERVICE