


Butt Weld Stub End (MSS Type A)





	SCHEDULE 10						SCHEDULE 40					
SIZE	DIMENSIONS						DIMENSIONS					
	Α	В	С	D	R	KG	Α	В	С	D	R	KG
1/2	34.9	21.3	50.8	2.11	3.2	0.08	34.9	21.3	50.8	2.77	3.2	0.12
3/4	42.8	26.6	50.8	2.11	3.2	0.09	42.8	26.6	50.8	2.87	3.2	0.15
1	50.8	33.4	50.8	2.77	3.2	0.14	50.8	33.4	50.8	3.38	3.2	0.19
1-1/4	63.5	42.1	50.8	2.77	4.8	0.21	63.5	42.1	50.8	3.56	4.8	0.26
1-1/2	73	48.1	50.8	2.77	6.4	0.25	73	48.1	50.8	3.68	6.4	0.38
2	92	60.3	63.5	2.77	7.9	0.38	92	60.3	63.5	3.91	7.9	0.54
2-1/2	104.8	73	63.5	3.05	7.9	0.47	104.8	73	63.5	5.16	7.9	0.80
3	127	88.9	63.5	3.05	9.5	0.64	127	88.9	63.5	5.49	9.5	1.13
4	157.2	114.3	76.2	3.05	11.1	0.98	157.2	114.3	76.2	6.02	11.1	1.81
5	185.7	141.3	76.2	3.4	11.1	1.24	185.7	141.3	76.2	6.55	11.1	2.54
6	215.9	168.3	88.9	3.4	12.7	1.95	215.9	168.3	88.9	7.11	12.7	3.72
8	269.7	219.1	101.6	3.76	12.7	2.61	33#3	-	3+2	-	(*)	-
10	323.9	273.1	127	4.19	12.7	4.54	() =)	-		-		-
12	381	323.9	152.4	4.57	12.7	7.05	55=5	-	(a)	- 4	14/	-

Our range of BUTT WELD Stub Ends are made to ANSI B16.9 and MSS SP43. They are available in schedule 10-40 thickness and 316/L or 304/L material grades.

Certificates are available upon request.





