



Normal bore/BSP thread size		Approx. Outside Diameter	Wall Thickness		Approx Inside Diameter		Weight per mtr. Plain ends	
			Medium SCH10	Heavy SCH40	Medium	Heavy	Medium	Heavy
SIZE	Imperial	mm	mm	mm	mm	mm	kgs	kgs
6mm	1/8"	10.2	2.0	2.6	6.2	5.0	0.40	0.49
8mm	1/4"	13.5	2.3	2.9	8.9	7.7	0.64	0.77
10mm	3/8"	17.2	2.3	2.9	12.6	11.4	0.84	1.02
15mm	1/2"	21.3	2.6	3.2	16.1	14.9	1.21	1.44
20mm	3/4"	26.9	2.6	3.2	21.7	20.5	1.56	1.87
25mm	1"	33.7	3.2	4.0	27.3	25.7	2.41	2.93
32mm	1 1/4"	42.4	3.2	4.0	36.0	34.4	3.1	3.79
40mm	1 1/2"	48.3	3.2	4.0	41.9	40.3	3.56	4.37
50mm	2"	60.3	3.6	4.5	53.1	51.3	5.03	6.19
65mm	2 1/2"	76.1	3.6	4.5	68.9	67.1	6.42	7.93
80mm	3"	88.9	4.0	5.0	80.9	78.9	8.36	10.30
100mm	4"	114.3	4.5	5.4	105.3	103.5	12.20	14.50
125mm	5"	139.7	5.0	5.4	129.7	128.9	16.60	17.90
150mm	6"	165.1	5.0	5.4	155.1	154.3	19.8	21.30

**We can thread any material from 1/4" up to 4" in BSP or NPT threads, with our machinery on site we can also offer a pipe cutting service up to 4" to any size you need using our specialist rigid cutting and threading machines.**



DELIVERY AS SOON AS NEXT DAY



EXPERT KNOWLEDGE OF THE INDUSTRY



WORLD CLASS CUSTOMER SERVICE